



WYE 3 Hots, 1 Neu, 1 Grnd

Technical Features	Catalog Number	
	STXP380Y10A	
Approval Standard	UL 1449 Edition 4 th	
Configuration	Wye, 3 hots, 1 Neu, 1 Grnd	
Technology	- TPMOV [®] (Intergrated Fuse Inside)	
Type of Connection	Parallel	
Frequency	47 – 63Hz	
Mode of Protection	10 Modes (L-N, L-L, L-G, N-G)	
Nominal Voltage	U_n	220/380VAC
Maximum Continuous Operating Voltage	U_c	L-N: 320VAC; L-L: 640VAC
Maximum Discharge Current (8/20)	I_{max}	100kA Per Phase; 50kA Per Mode
Nominal Discharge Current (8/20)	I_n	20kA
Voltage Protection Level at 6kV, 3kA	U_p	L-N: 1200V; N-G: 600V
Measured Limited Voltage 2kV, 67A		L-N: 25V; N-G: 15V
Response Time (all modes)	t_A	1ns
Temporary Overvoltage Characteristics	U_T	L-N: 410V/5s; N-G: 425V/5s
Short Circuit Current Rating (SCCR)	I_{sc}	200kA
Filter		No
Indicator		LED Status Indicator: Phase Loss Indication; Audible Alarm; Dry Contact
Surge Counter		No
Multi Discharge System		Yes
Remove impulse voltage technology		Standard sinewave for electrical system
Leakage Current		No
Degree of Protection		NEMA 4X Non-metallic
Enclosure material		UL94-5VA
Mounting On		Panel
Wire Range		1.5mm ² to 25mm ² (Flexible)/ 35mm ² (Rigid)
Terminal Torque		14.75 lb - in / 1.67 N - m
Operating Temperature		-40°C to +85°C
Humidity Range		0 - 95%
Warranty		10 Years

Dimensions and Mounting Configurations

